## A-Lock mechanical



A-Lock mechanical - quick change of attachments without hydraulic supply

For excavators without hydraulic circuits at the boom

Simple locking mechanism

NEW: No parts jut out sideways, improved use with slender buckets 1)

Integrated carry hook 2)

Can be refitted to hydraulic A-Lock Compact Plus 1)

Safeguarding of the locking bolt, optical control

Tool for opening is included in accessoiries 1)

1) concernes Cl 3 and 3 Combi, which are made in "Compact"-style 2) Class 01 and 1 only with loading eye







## Technical details

## **Advantages**

Fits to any type of excavator

Form locking system


Pin to point distance is the same as with OEM bucket

Safeguarding of the locking by spring born flap (3, 3 Combi) respectively fastener for the locking hand gear (Class 01,1,2 and 2 C)  $\,$ 

Open / close with 1 ½ rotations (540°)















Available in following classes:

Class	CI 01	CI 1	CI 2	CI 2 C	CI 3	CI 3 C
Exc.weight, to*	< 3,5	3,5 - 6	6 - 10	10 - 12	12 - 24	24 - 38

 $<sup>^{*}</sup>$  This classification is only a rough recommendation. Class 3 and 3 Combi is in "Compact" style with hexagonal top.

All rights as well as printing errors reserved.

Version 0110

WIMMER Hartstahl GmbH.&Co.KG. und WIMMER Felstechnik GmbH.
Industriestraße 3, A-5303 Thalgau, AUSTRIA, Tel.: +43 (0)6235 6655 0, Fax.: +43 (0)6235 6655 18
WIMMER Canada Inc., 6683 Jean Talon Est, Suite 432,Saint Leonard, QC, H1S 0A5, Canada US phone line: 8778379240
Wimmer International CZ s.r.o., Rudolfovská 170 a, 370 01 České Budějovice, Tel.: +420 387 203 735, Fax +420 387 203 736

www.wimmer.info office@wimmer.info

Auth. WIMMER dealer:

