A-Lock Oilmatic



Change of hydraulic tools with highest comfort and speed

Quality without Compromise.

Automatic coupling of hydraulic circuits when attaching the tools

Automatic tool identification and activation of leakage oil line

Coupling mechanism placed inside, protected against dirt or damage

All tools with A- Lock system can be used furthermore

2-step operation protects hydraulic couplers

Automatic pressure release

SPS control

Tension free cast iron body







Technical details

Advantages

Coupling 1 or 2 hydraulic circuits from operator's cabin

For tools with or without hydraulic functions (automatic detection)

For each kind of hydraulic excavator with 12 tons or more

Form locking system

Coupling under pressure possible

Can even be used at very low temperature (until -20° C)



The Oilmatic Box: Brain of the oilmatic system with integated acoustic locking control.



Working hours of eight various tools can be recorded.

Available in following classes:

Class	CI 3	Cl 3 Combi
Exc. weight, to*	12 - 24	24 - 38

^{*} This classification is only a rough recommendation, it depends on individual parameters.



A-Lock OII MATIC with attachments





Couplings at the coupler

Couplings at the tool



2-step operation: Only when a tight connection between coupler and tool is established, the couplings drive out and connect the circuits (within parts of a second).

All rights and errors reserved

Version 0307

WIMMER Hartstahl GmbH. & Co.KG. und WIMMER Felstechnik GmbH. Industriestraße 3, A-5303 Thalgau, AUSTRIA, Tel.: ++43 (0)6235 6655 0, Fax.: ++43 (0)6235 6655 18 WIMMER Canada Inc., 9999, Boul. Parkway, Anjou, (QC) CANADA HIJ 1P7, Tel.: ++ 514 355 64 24 Wimmer Budejovice, Ruldolfovská 170 a, 37 001 Ceské Budejovice, Tel.: ++420 387 203 735, Fax ++420 387 203 735

www.wimmer.info office@wimmer.info

Auth. WIMMER Dealer:



Quality without Compromise.